



- See page 11 for technical features
- Standard seal "TC" – felt strip, see page 04. For seal types TA and TG, the dimensions are maintained. **Should a different type of seal be requested, the dimensions of the columns "L", "N" and "M" on the table can be modified**, but our engineering department should be consulted for more information.
- For applications with different bearing types and different shaft diameters please consult our Engineering Department.
- **Specification example:** SNAH-516-BP-TG, for 22216-K bearing = SNAH housing, size 516, made of grey cast iron with 2 holes on the base, prepared for 22216-K bearing and H-316 adapter sleeve, for locating bearing and passing shaft, with TG split nitrile or polyurethane rubber retainer with double lips seal.
- This bearing series can be supplied with solid base in nodular cast iron, with 2 or 4 holes on the base. These housings are identified by the prefix SSNAHD. Use suffix MS1 for two holes on the base and suffix MS2 for four holes on the base. Example: SSNAHD-516-LC-TG-MS2. Please consult our Engineering Department for dimensions and location of the holes.

BC - Locating bearing, blind shaft

LC - Non-locating bearing, blind shaft



Housing	d	Bearing	Adapter sleeve	Dimensions (mm)											Ring Dim.	FRB Qtt	Weight (kg)
				H	E	A	B	C	L	N	N1	P	S	V			
SNAH 505	20	1205K	H 205												5/52	2	
		2205K	H 305	40	130	165	46	18	67	20	15	74	12	19	3,5/52	2	1,5
		22205K	H 305												3,5/52	2	
SNAH 506	25	1206K	H 206												8/62	2	
		2206K	H 306	50	150	185	52	19	77	20	15	89	12	22	6/62	2	2
		22206K	H 306												6/62	2	
SNAH 507	30	1207K	H 207												8,5/72	2	
		2207K	H 307	50	150	185	52	21	82	20	15	93	12	22	5,5/72	2	2,2
		22207K	H 307												5,5/72	2	
SNAH 508	35	1208K	H 208												10,5/80	2	
		2208K	H 308	60	170	205	60	22	85	20	15	107	12	25	8/80	2	2,9
		22208K	H 308												8/80	2	
SNAH 509	40	1209K	H 209												5,5/85	2	
		2209K	H 309	60	170	205	60	23	85	20	15	109	12	25	3,5/85	2	2,9
		22209K	H 309												3,5/85	2	
SNAH 510	45	1210K	H 210												10,5/90	2	
		2210K	H 310	60	170	205	60	24	90	20	15	113	12	25	9/90	2	3,2
		22210K	H 310												9/90	2	
SNAH 511	50	1211K	H 211												11,5/100	2	
		2211K	H 311	70	210	255	70	26	95	24	18	127	16	28	9,5/100	2	4,4
		22211K	H 311												9,5/100	2	
SNAH 512	55	1212K	H 212												13/110	2	
		2212K	H 312	70	210	255	70	28	105	24	18	133	16	30	10/110	2	5,1
		22212K	H 312												10/110	2	
SNAH 513	60	1213K	H 213												14/120	2	
		2213K	H 313	80	230	275	80	31	110	24	18	148	16	30	10/120	2	6,5
		22213K	H 313												10/120	2	
SNAH 515	65	1215K	H 215												15,5/130	2	
		2215K	H 315	80	230	280	80	32	115	24	18	154	16	30	12,5/130	2	7
		22215K	H 315												12,5/130	2	
SNAH 516	70	1216K	H 216												16/140	2	
		2216K	H 316	95	260	315	90	35	120	28	22	175	20	32	12,5/140	2	9,5
		22216K	H 316												12,5/140	2	
SNAH 517	75	1217K	H 217												16,5/150	2	
		2217K	H 317	95	260	320	90	37	125	28	22	183	20	32	12,5/150	2	10
		22217K	H 317												12,5/150	2	
SNAH 518	80	1218K	H 218												17,5/160	2	
		2218K	H 318	100	290	345	100	46	140	28	22	193	20	35	12,5/160	2	12,5
		22218K	H 318												6,25/160	2	
SNAH 519	85	1219K	H 219												18/170	2	
		2219K	H 319	112	290	345	100	42	145	28	22	210	20	35	12,5/170	2	13,7
		22219K	H 319												12,5/170	2	
SNAH 520	90	1220K	H 220												18/180	2	
		2220K	H 320	112	320	380	110	50	160	32	26	215	24	40	12/180	2	17,6
		22220K	H 320												4,85/180	2	
SNAH 522	100	1222K	H 222												21/200	2	
		2222K	H 322	125	350	410	120	58	175	32	26	239	24	45	13,5/200	2	22
		22222K	H 322												5,1/200	2	
SNAH 524	110	1224K	H 324												22/215	2	
		2224K	H 324	140	350	410	120	62	185	32	26	271	24	45	14/215	2	26
		22324K	H 324												5/215	2	
SNAH 526	115	1226K	H 326												13/230	2	
		2226K	H 326	150	380	445	130	65	190	35	28	290	24	50	5/230	2	33
		22228K	H 328												15/250	2	
SNAH 528	125	1232K	H 328												5/250	2	40
		2232K	H 330	150	420	500	150	70	205	42	35	302	30	50	16,5/270	2	
		22323K	H 330												5/270	2	49
SNAH 530	135	1232K	H 332												17/290	2	
		22323K	H 332	170	470	550	160	82	235	42	35	344	30	60	5/290	2	55
		22323K	H 332														