



BC - Locating bearing, blind shaft




LC - Non-locating bearing, blind shaft

- See page 14 for technical features.
- Standard seal "TC" – felt strip, see page 04.
- **Specification example:** F-515-BC + 1 FRB-10/130 = F-500 housing, size 515, made of grey cast iron, for locating bearing and blind shaft, for bearings type 2215-K or 22215-K.
- When ordering, always indicate the bearings or locating rings used.
- For shafts with diameters in inches please contact our engineering department and specify on order form, otherwise it shall be manufactured in millimeters, as it is the standard measure for this series.
- One felt strip for housing type A and two felt strips for housing type B should be used.





BP - Locating bearing, passing shaft




LP - Non-locating bearing, passing shaft


Housing	Shaft d	Bearing designation	Adapter sleeve	Lock ring		Dimensions (mm)												Felt	Weight (kg)
				Qty.	Specification	AA	AB	A1	Ba	Bb	D1	H	H1	E	L	S	U		
F-505	20	1205K	H 205	1	FRB 5/52													FS110	1,1
		2205K	H 305	1	ZW 42x52	51,5	56,5	10	15	12,5	75	100	38	96	110	10	45		
		22205K	H 305	1	ZW 42x52														
F-506	25	1206K	H 206	1	FRB 6/62													FS190	1,5
		2206K	H 306	1	ZW 50x62	57	59,5	12	16	15	86	117	44	116	130	10	49		
		22206K	H 306	1	ZW 50x62														
F-507	30	1207K	H 207	1	FRB 8/72													FS190	1,8
		2207K	H 307	1	ZW 65x72	59,5	63,5	12	16	14,5	97	130	48,5	130	145	12	52		
		22207K	H 307	1	ZW 65x72														
F-508	35	1208K	H 208	1	FRB 7/80													FS190	2,9
		2208K	H 308	1	ZW 70x80	64	65,5	12	17	18	108	143	54	140	160	12	53,5		
		22208K	H 308	1	ZW 70x80														
F-509	40	1209K	H 209	1	FRB 6/85													FS190	3,1
		2209K	H 309	1	ZW 75x85	64,5	69,5	12	19	16,5	113	160	60	160	180	12	56		
		22209K	H 309	1	ZW 75x85														
F-510	45	1210K	H 210	1	FRB 5/90													FS190	3,8
		2210K	H 310	1	ZW 80x90	68,5	73	15	22	17,5	118	160	60	160	180	12	61		
		22210K	H 310	1	ZW 80x90														
F-511	50	1211K	H 211	1	FRB 6/100													FS260	4
		2211K	H 311	1	ZW 85x100	75,5	81,5	15	24	19,5	128	172	65	170	192	12	66		
		22211K	H 311	1	ZW 85x100														
F-512	55	1212K	H 212	1	FRB 8/110													FS260	4,6
		2212K	H 312	1	ZW 90x110	77	82	15	23	19	142	189	72	180	210	12	68		
		22212K	H 312	1	ZW 90x110														
F-513	60	1213K	H 213	1	FRB 10/120													FS260	6
		2213K	H 313	1	FRB 2/120	80	86	15	22	20	152	203	78	190	225	12	71		
		22213K	H 313	1	FRB 2/120														




BC - Locating bearing, blind shaft



LC - Non-locating bearing, blind shaft



BP - Locating bearing, passing shaft



LP - Non-locating bearing, passing shaft

- See page 14 for technical features.
- Standard seal "**TC**" – felt strip, see page 04.
- **Specification example:** F-515-BC + 1 FRB-10/130 = F-500 housing, size 515, made of grey cast iron, for locating bearing and blind shaft, for bearings type 2215-K or 22215-K.
- When ordering, always indicate the bearings or locating rings used.
- For shafts with diameters in inches please contact our engineering department and specify on order form, otherwise it shall be manufactured in millimeters, as it is the standard measure for this series.
- One felt strip for housing type A and two felt strips for housing type B should be used.

Housing	Shaft d	Bearing designation	Adapter sleeve	Lock ring		Dimensions (mm)											Felt	Weight (kg)
				Qty.	Specification	AA	AB	A1	Ba	Bb	D1	H1	E	L	S	U		
F-515	65	1215K	H 215	2	FRB 8/130												FS260	10
		2215K	H 315	1	FRB 10/130	104	104	25	30	27	168	95	152	190	16	93		
		22215K	H 315	1	FRB 10/130													
F-516	70	1216K	H 216	2	FRB 8,5/140												FS330	10,3
		2216K	H 316	1	FRB 10/140	110	110	25	31	30	176	98	152	196	16	96		
		22216K	H 316	1	FRB 10/140													
F-517	75	1217K	H 217	2	FRB 9/150												FS330	12,6
		2217K	H 317	1	FRB 10/150	114	114	25	31	30	188	105	170	210	16	72		
		22217K	H 317	1	FRB 10/150													
F-518	80	1218K	H 218	2	FRB 10/160												FS330	13
		2218K	H 318	1	FRB 10/160	118	118	25	30	31	198	105	170	210	16	105		
		22218K	H 318	1	FRB 10/160													
F-520	90	1220K	H 220	2	FRB 11/180												FS370	20
		2220K	H 320	1	FRB 10/180	127	127	30	30	33	224	125	198	250	20	113		
		22220K	H 320	1	FRB 10/180													
F-522	100	1222K	H 222	2	FRB 12,5/200												FS460	22
		2222K	H 322	1	FRB 10/200	137	137	30	30	38	246	135	219	270	20	123		
		22222K	H 322	1	FRB 10/200													